

APPROVED PROVIDER TO THE
UTILITIES & ENERGY SECTOR



WORKING AT HEIGHTS? ERGODYNE'S DROPPED OBJECTS PREVENTION



PRODUCTION
TIME



INJURIES
18,000+



DEATHS
24

230 WORK SITE DEATHS
IN THE LAST DECADE
...AND WHO KNOWS
HOW MANY CLOSE
CALLS

2021-2022 // AUSTRALIA & NEW ZEALAND REPORTS ————— FALLING & MOVING OBJECTS / WWW.SAFEWORKAUSTRALIA.GOV.AU / WWW.AIHW.GOV.AU / WWW.DATA.WORKSAFE.GOV.TZ

CREATE A DROP FREE ZONE WITH THESE INDUSTRY LEADING
PRODUCTS SPECIALISED FOR POWER AND UTILITY COMPANIES

TOOL LANYARD

3129 Tool Lanyard Double-Locking Single Carabiner

- Non-shock absorbing webbing
- Designed to be attached to structures
- Single length construction eliminates weak points
- Convenient non-slip control
- Double-action locking carabiner
- Swivelling carabiner prevents tangles
- Heavy-gauge nylon stitching for strength and durability
- Third party certified to 2:1 safety factor
- Lanyard dimensions: 193cm

SKU:19137



3129

TOOL LANYARD

3109F(x) Double-Locking Single Carabiner Tool Lanyard + Swivel

- Shock absorbing
- Durable 1680 denier polyester elastic
- Low profile lightweight design reduces snag hazards
- Anodized aluminium alloy swivelling carabiner
- Single length construction eliminates weak points
- Third party certified to 2:1 safety factor
- Lanyard dimensions: 96-122cm

SKU:19809



3109F(x)

*REFERENCES AVAILABLE UPON REQUEST

FOR YOUR FREE WORKSITE TRIAL GET IN CONTACT WITH THE PRYME TEAM TODAY.



www.pryme.com.au | +61 7 3374 4544 | sales@pryme.com.au



APPROVED PROVIDER TO THE UTILITIES & ENERGY SECTOR



DROP FREE ZONE

LUCK IS BAD POLICY

DROPS WILL HAPPEN

KEEP YOUR WORKERS SAFE

ACCESSORIES

3175 Accessory Anchor

- Heavy-duty 45mm polyester webbing
- Nickel-plated iron D-Ring
- 840D nylon wear protector sleeve
- Not for climbing or fall arrest
- Length 60cm
- Used with Tape Trap; creates retrofit connection point
- Static anchor maximum safe working capacity: 181kg
- Tool Tail maximum safe working capacity: 18kg



3175

SKU:19175

TOOL LANYARD

3101 Single Carabiner Stainless Steel Tool Lanyard

- Energy absorbing cord with tubular nylon webbing
- Manual locking stainless steel carabiners (#304)
- Captive eye carabiner
- Reflective accent for higher visibility
- Lock stitching at both ends
- Third-party certified to a 2:1 safety factor
- Length: 107cm-137cm



3101

SKU:19017

TOOL BAG

5960 Canvas Hoist Bucket + D-Rings 68kg

- 24 oz. canvas main material
- Synthetic leather reinforced base
- Zinc plated alloy steel d-ring for hoisting
- Heavy-gauge nylon stitching
- Maximum safe tool tether anchor capacity: 9kg on each d-ring
- Third-party certified to a 5:1 safety factor
- Dimensions: 32cm D x 43cm H



5960

SKU:14960

RETROFIT TOOL TAILS

3713 Elastic Loop Tool Tails Swivel - 3-Pack

- Plated swivelling connection
- Stretch cord with tubular nylon webbing
- Tool traps create retrofit tether point
- Doubles as an anchor loop for belt, harness or separate structure
- Third-party certified to a 2:1 safety factor
- Adjustable barrel lock for tool attachment
- Fully enclosed O-ring
- Length: 38cm



3109F(x)

SKU:19765

*REFERENCES AVAILABLE UPON REQUEST

FOR YOUR FREE WORKSITE TRIAL GET IN CONTACT WITH THE PRYME TEAM TODAY.



www.pryme.com.au | +61 7 3374 4544 | sales@pryme.com.au